



Designed by Stefano Casciani, the Aliante pendant is a direct/indirect sculptural linear fluorescent or LED luminaire that works in a variety of areas in both commercial and residential applications.

Features and capacities

- Canopy and aesthetic shell: Constructed using stamped aluminum
- Inner reflector: Mirrored aluminum
- Suspension: Streamlined cable system that integrates an insulated current-carrying wire with exterior braided stainless steel sheath. UL approved. Adjustable for up to a 12 ft/366 cm or 16 ft/488 cm high ceiling. Longer lengths available upon request. Pole versions also available.
- Lens (direct/indirect only): Translucent acrylic
- LED: 95 CRI in 2700K, 3000K, or 3500K
- Fluorescent lamp: 1 or 2 54 W T5 HO or 28 W T5 HE fluorescent lamp (not included)
- Sockets: Twist-lock installation
- Controls: EcoSystem™, 3-wire, 2-wire, and non-dim options
- Junction box: 4 in (10 cm) octagonal or round supplied by others. Requires fixture brace for suspended ceilings.
- Weight: Cable version—12 lbs (5.5 kg)

Typical applications

- Commercial: Boardrooms, video conferencing rooms, executive offices and dining rooms, reception, bar, cash register areas, art spaces
- Residential: Kitchen island (not for use over cooktop or grill); kitchen table, dining room, home office, and wet bar

Dimensions and mounting

- Mounting: Chassis mounting system for easy installation
- Length: 4 ft and 5 ft (121.92 and 152.4 cm)

Color

- Automotive paint interior only (available in gloss and matte finishes)

Related components

- Grille option kit: Includes clear or frosted polycarbonate disks coated with a silicone hardcoat and tension rods with spacers. Order this kit separately from the main unit

Technical documents available at www.lutron.com/ivalo.

How to order an Aliante pendant

Example model number

A P N 60 L 35 2 2 3 U GT MT
 1 2 3 4 5 6 7 8 9 10 11 12

Fixture Options

1 Family

A = Aliante

2 Fixture type

P = Pendant

3 Light orientation

N = Indirect

D = Direct/Indirect

4 Length

48 = 48 in (4 ft)

60 = 60 in (5 ft)

5 Lamps

1 = 1 Lamp

2 = 2 Lamp

L = LEDs, 95 CRI

6 Lamp type

27¹ = 44 W 1670lm (4 ft), 57 W 2200lm (5 ft), 2700 K

30¹ = 44 W 1670lm (4 ft), 57 W 2200lm (5 ft), 3000 K

35¹ = 44 W 1670lm (4 ft), 57 W 2200lm (5 ft), 3500 K

2F = 28 W, 4 ft T5HE FI

3F² = 35 W, 5 ft T5HE FI

5F = 54 W, 4 ft T5HO FI

8F³ = 80 W, 5 ft T5HO FI

7 Voltage

2 = 120 V~

3⁴ = 347 V~

4 = 220 V~/240 V~

7 = 277 V~

8 Suspension

2 = Cable 12 ft Ceiling

6 = Cable 16 ft Ceiling

P = Pole

9 Control option

N = Non-Dim

2⁵ = 1% 2-Wire

3 = 1% 3-Wire

E = 1% EcoSystem

10 Region

U = UL – North America

I = International

11 Canopy finish 12 Shell finish

GT = Gloss Titanium

MT = Matte Titanium

GG = Gloss Graphite

MG = Matte Graphite

GS = Gloss Slate

MS = Matte Slate

GC = Gloss Copper

MC = Matte Copper

GF = Gloss Flame

MF = Matte Flame

GL = Gloss Lapis

ML = Matte Lapis

GE = Gloss Ebony

ME = Matte Ebony

GA = Gloss Arctic White

MA = Matte Arctic White

GP = Gloss Pearl White

MP = Matte Pearl White

AN = Brushed Anodized Clear

AB = Brushed Anodized Black

PS = Silver

PM = Metallic Silver

PB = Bronze

Custom color, hanging, and fixture options available. Contact fixtures customer service at fixtures@lutron.com.

¹ LED only

² 10% dimming

³ Non-dim only

⁴ T5/non-dim only

⁵ LED/120V~ only