



Designed by Lewis.Tsurumaki.Lewis Architects, the Rotare pendant is a direct/indirect sculptural linear fluorescent or LED luminaire that distributes light broadly and smoothly.

Features and capacities

- Canopy: Chassis in Dark Grey. Cover in Matte Automotive Paint
- Fixture shell: Constructed using stamped steel
- Inner reflector: Mirrored aluminum
- Suspension: Streamlined cable system that integrates an insulated current-carrying wire with exterior braided stainless steel sheath. UL approved. Adjustable for up to a 12 ft/366 cm or 16 ft/488 cm high ceiling. Longer lengths available upon request. Pole versions also available.
- Lens: 0.020 in (.5mm) thick white translucent acrylic film
- LED: 95CRI in 2700 K, 3000K, or 3500 K
- Fluorescent lamp: Two 54 W T5 HO or 28 W T5 HE fluorescent lamps (not included)
- Sockets: Twist-lock installation
- Controls: EcoSystem™, 3-wire, 2-wire, and non-dim options

- Junction box: 4 in (10 cm) octagonal or round supplied by others. Requires fixture brace for suspended ceilings.
- Weight: 21 lbs (8.2 kg)

Typical applications

Boardrooms, video conferencing rooms, executive offices and dining rooms, reception, bar, cash register areas, and art spaces

Dimensions and mounting

- Mounting: Proprietary chassis mounting system for easy installation
- Length: 4 ft 4 in (134.11 cm)

Color

- Automotive paint interior only (available in gloss and matte finishes)

Technical documents available at www.lutron.com/ivalo.

How to order a Rotare pendant

Example model number

R P D 48 L 35 2 2 2 U GT MT
 1 2 3 4 5 6 7 8 9 10 11 12

Fixture Options

1 Family

R = Rotare

2 Fixture type

P = Pendant

3 Light orientation

D = Direct/Indirect

4 Length

48 = 48 in (4 ft)

5 Lamps

2¹ = 2 Lamp

L² = LEDs, 95 CRI

6 Lamp type

27² = 85 W, 3400lm, 2700 K

30² = 85 W, 3400lm, 3000 K

35² = 85 W, 3400lm, 3500 K

2F = 28 W, 4 ft T5HE FI

5F = 54 W, 4 ft T5HO FI

7 Voltage

2 = 120V~

4 = 220V~/240V~

7 = 277V~

8 Suspension

2 = Cable 12 ft Ceiling

6 = Cable 16 ft Ceiling

9 Control option

N = Non-Dim

2³ = 1% 2-Wire

3 = 1% 3-Wire

E = 1% EcoSystem

10 Region

U = UL – North America

I = International

11 Canopy finish 12 Shell finish

GT = Gloss Titanium

GG = Gloss Graphite

GS = Gloss Slate

GC = Gloss Copper

GF = Gloss Flame

GL = Gloss Lapis

GE = Gloss Ebony

GA = Gloss Arctic White

GP = Gloss Pearl White

PS = Silver

PM = Metallic Silver

PB = Bronze

MT = Matte Titanium

MG = Matte Graphite

MS = Matte Slate

MC = Matte Copper

MF = Matte Flame

ML = Matte Lapis

ME = Matte Ebony

MA = Matte Arctic White

MP = Matte Pearl White

¹ T5 only

² LED only

³ LED/120V~ only

Custom color, hanging, and fixture options available. Contact fixtures customer service at fixtures@lutron.com.