



The Aliante Sconce is a wall mounted, direct/indirect or indirect sculptural linear fluorescent or LED luminaire designed by Stefano Casciani, which can be mounted vertically, horizontally, or at an angle.

Features and capacities

- Fixture shell: Constructed using stamped aluminum
- Inner reflector: Mirrored aluminum
- Lens (direct/indirect only): Translucent acrylic
- LED: 95 CRI in 2700K, 3000K, or 3500K
- Fluorescent lamp: 1 or 2 54W T5 HO or 28W T5 HE fluorescent lamp (not included)
- Sockets: Twist-lock installation
- Controls: EcoSystem™, 3-wire, 2-wire, and non-dim options
- Junction box: 4 in (10 cm) octagonal or round supplied by others
- Weight: 11 lbs (5 kg)
- ADA compliant: Designed to protrude less than 4 in from the wall

Typical applications

- Commercial: Elevator and office lobbies, hallways, stairwells, reception areas, executive offices, flanking or crowning doorways
- Residential: Entry halls, stairwells, flanking or crowning doorways

Dimensions and mounting

- Stainless Steel wall mounting system and paper template for easy installation. Side hinges with captured locking screws for easy lamp replacement. For wall mounting only
- Length: 48 in and 60 in (121.92 cm and 152.4 cm)

Color

- Automotive paint interior only (available in gloss and matte finishes), powder coat (required for exterior applications)

Technical documents available at www.lutron.com/ivalo.

How to order an Aliante sconce

Example model number

A E N 60 L 35 2 W 2 U PS MT
 1 2 3 4 5 6 7 8 9 10 11 12

Fixture Options

1 Family

A = Aliante

2 Fixture type

N = Interior Sconce
 E¹ = Exterior Sconce

3 Light orientation

N = Indirect
 D = Direct/Indirect

4 Length

48 = 48 in (4 ft)
 60 = 60 in (5 ft)

5 Lamps

1 = 1 Lamp
 L = LEDs, 95 CRI

6 Lamp type

27² = 44 W 920lm (4 ft), 57 W 1090lm (5 ft), 2700K
 30² = 44 W 920lm (4 ft), 57 W 1090lm (5 ft), 3000K
 35² = 44 W 920lm (4 ft), 57 W 1090lm (5 ft), 3500K
 2F = 28 W, 4 ft T5HE FI
 3F³ = 28 W, 4 ft T5HE FI
 5F = 54 W, 4 ft T5HO FI
 8F¹ = 54 W, 4 ft T5HO FI

7 Voltage

2 = 120V~
 3⁴ = 347V~
 4 = 220V~/240V~
 7 = 277V~

8 Suspension

W = Wall Mount

9 Control option

N = Non-Dim
 2⁵ = 1% 2-Wire
 3 = 1% 3-Wire
 E = 1% EcoSystem

10 Region

U = UL – North America
 I = International

11 Chassis finish

PS = Silver

12 Shell finish

GT = Gloss Titanium	MT = Matte Titanium
GG = Gloss Graphite	MG = Matte Graphite
GS = Gloss Slate	MS = Matte Slate
GC = Gloss Copper	MC = Matte Copper
GF = Gloss Flame	MF = Matte Flame
GL = Gloss Lapis	ML = Matte Lapis
GE = Gloss Ebony	ME = Matte Ebony
GA = Gloss Arctic White	MA = Matte Arctic White
GP = Gloss Pearl White	MP = Matte Pearl White
AN = Brushed Anodized Clear	
AB = Brushed Anodized Black	
PS = Silver	
PM = Metallic Silver	
PB = Bronze	

Custom color, hanging, and fixture options available. Contact fixtures customer service at fixtures@lutron.com.

¹ Non-dim only
² LED only
³ 10% dimming
⁴ T5/non-dim only
⁵ LED/120V~ only