



Winka Dubbeldam designed the Inflection sconce, an indirect sculptural compact fluorescent or LED luminaire that can be wall or ceiling (flush) mounted.

Features and capacities

- Fixture housing shell: Constructed using frosted vacuum-formed polycarbonate and a stamped aluminum inset
- LED: Red, green, blue, amber or white (2700K or 3500K)
- CFL: One 42W triple tube compact fluorescent lamp (not included)
- Sockets: Twist-lock for CFL configuration. LED module is hard-wired and designed to last the lifetime of the fixture
- Controls: EcoSystem™, 3-wire, 2-wire, and non-dim options
- Junction box: 4 in (10 cm) octagonal, round, or rectangular switch box supplied by others
- Weight: 5.2 lbs (2.3 kg)
- ADA compliant: Designed to protrude less than 4 in from the wall

Typical applications

- Building, elevator, office lobbies, hallways, stairwells, reception areas, and executive offices, as well as flanking doorways, entry halls, and theaters

Dimensions and mounting

- Mounting: Steel wall mounting system with multiple mounting holes for easy installation and lamp replacement
- Locking screws keeps cover shell tightly fastened.
- ADA compliant. Designed to protrude less than 4 in (10 cm) from wall. For wall mounting or flush mounted ceiling fixture (LED only).
- Length: 23 in (584.2 mm)

Color

- Automotive paint interior only (available in gloss and matte finishes), powder coat (required for exterior applications)

Technical documents available at www.lutron.com/ivalo.

How to order an Inflection sconce

Example model number

N N N 23 1 42 2 W N U WH GT
 1 2 3 4 5 6 7 8 9 10 11 12

Fixture Options

1 Family

N = Inflection

2 Fixture type

N = Interior Sconce

3 Light orientation

N = Indirect

4 Length

23 = 23 in

5 Lamps

1¹ = 1 lamp

L = LEDs, 95 CRI

6 Lamp type

42¹ = 42W CFL

AL² = 12 W, Amber

BL² = 12 W, Blue

GL² = 12 W, Green

RL² = 12 W, Red

NL² = 12 W, 3500K

WL² = 12 W, 2700K

7 Voltage

2 = 120V~

4 = 220V~/240V~

7 = 277V~

8 Suspension

W = Wall Mount

9 Control option

N = Non-Dim

2³ = 1% 2-wire

3⁴ = 1% Dim 3-Wire

E⁴ = EcoSystem

10 Region

U = UL – North America

I = International

11 Chassis finish

WH = White

12 Shell finish

GT = Gloss Titanium

GG = Gloss Graphite

GS = Gloss Slate

GC = Gloss Copper

GF = Gloss Flame

GL = Gloss Lapis

GE = Gloss Ebony

GA = Gloss Arctic White

GP = Gloss Pearl White

PS = Silver

PM = Metallic Silver

PB = Bronze

MT = Matte Titanium

MG = Matte Graphite

MS = Matte Slate

MC = Matte Copper

MF = Matte Flame

ML = Matte Lapis

ME = Matte Ebony

MA = Matte Arctic White

MP = Matte Pearl White

¹ CFL only

² LED only

³ LED/120V~ only

⁴ CFL is 5% dimming

Custom color, hanging, and fixture options available. Contact fixtures customer service at fixtures@lutron.com.