

CS510 / CS610 : DUAL CONE CEILING SPEAKER W ABS ENCLOSURE

Available in 5" and 6" of driver size complete with matching transformer of three tappings ; 1, 3 or 6W. Back enclosure are supplied as integral part of the speakers made from quality ABS plastic. Installation is made easy with its screw mounting mechanism.

Packing information

CS510A : 850 (W) x 385 (H) x 240 (D) mm
: 15 kg
: 20 uts per carton

CS610A : 685 (W) x 475 (H) x 340 (D) mm
: 19.6 kg
: 18 uts per carton



CS510A - 5" 6W 100V Line
CS610A - 6" 6W 100V Line



CS606 - 6" 6W 100V Line

CS515 : DUAL CONE CEILING SPEAKER W ABS ENCLOSURE

CS515 is a general purpose 5" 6W 100V line ceiling speakers which comes complete with ABS honeycome grille and back enclosure. It is suitable for BGM and Paging application and suitable for rust prove enviroment.

Packing information

CS515 : 850 (W) x 385 (H) x 240 (D) mm
: 15 kg
: 20 uts per carton



CS515 - 5" 6W 100V Line

NEW

CS606 : DUAL CONE CEILING SPEAKER W METAL ENCLOSURE

Available in 6" dual cone speaker with back metal enclosure, grill and baffle and multi tap matching transformer of 1.5, 3 and 6W 100V line. This model shall be suitable for installations that demand fire resistant version of dome.

Packing information

CS606 : 420 (W) x 220 (H) x 345 (D) mm
: 6.5 kg
: 6 uts per carton

CS343 : WEATHERPROOF CEILING SPEAKER

CS343 is driven by a 4" dual cone speaker with built in matching transformer of dual taps of 3 and 6W 100V line.

Made of quality ABS enclosure and aluminum grille, it is suitable for high humidity areas, such as bathrooms and salty environment. Though compact in size, it delivers satisfactory sound reproduction with high SPL level, good for listening pleasure as well as paging clarity.

Packing information

CS343 : 550 (W) x 180 (H) x 465 (D) mm
: 9.5 kg
: 9 uts per carton



CS343 - 4" 6W 100V Line

Technical Specifications

	CS510	CS610	CS606	CS515	CS343
SPEAKER					
Power rating	6W 100V line nominal (max 10W)				
Diameter	5" (125 mm)	6" (150 mm)		5" (125 mm)	4" (100 mm)
Cone type	Dual cone				
Impedance (Ohm)	8				
Freq response (+/- 5dB)	150 ~ 19 KHz	120 ~ 19 KHz	150 ~ 16 KHz	150 ~ 17 KHz	150 - 18 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz	93 dB	92 dB	91 dB	92 dB	90 dB
Magnet weight	3 oz	5.3 oz	2 oz	3 oz	
TRANSFORMER					
Tapping (100V line)	1 / 3 / 6W		1.5 / 3 / 6W		3 / 6W
Primary impedance (Ohm)	10 K / 3.3 K / 1.6 K		6.7 K / 3.3 K / 1.6 K		10 K / 3.67 K / 1.7 K
Secondary impedance (Ohm)	8				
PHYSICAL					
Grille / enclosure	White metal / ABS white		White metal	ABS Plastic	Aluminum / ABS
Cutting hole dim	140 mm	175 mm	165 mm	145 mm	120 mm
Overall size (dia x height)	177 x 130 mm	230 x 102 mm	200 x 100 mm	175 x 95 mm	140 x 130 mm
Weight	715 g	785 g	950 g	600 g	900 g
Colour	White				

