

SURFACE MOUNT SPEAKER

It is constructed with high quality ABS plastic with 4" dual cone speaker driver and multi tapping matching transformer of 1 / 3 / 6 and 10W 100 V line. Suitable for wall and ceiling installation with optional tilt mounting bracket. Available in white colour.

Packing information

BS410 : 550 (W) x 220 (H) x 430 (D) mm
: 12 kg
: 12 uts per carton



BS410 - 4" 10W 100V

SURFACE MOUNT SPEAKER

A classic yet favourite model which is suitable for installations in small enclosed areas such as staircase, office, etc. Available in white colour with multi tap matching transformer of 1 / 3 / and 6W 100V line, fit for vertical or horizontal installations.

Packing information

DV410 : 590 (W) x 400 (H) x 305 (D) mm
: 15.4 kg
: 18 uts per carton



DV410 - 4" 6W 100V

SURFACE MOUNT SPEAKER

Wall mount speaker are suitable for any type of sound reproduction, for both paging and background music. Available in white colour with high efficiency driver and line transformers.

Packing information

BS410 : 550 (W) x 220 (H) x 430 (D) mm
: 12 kg
: 12 uts per carton



NEW

BS506 - 5" 6W 100V

Technical Specifications

	BS410	DV410	BS506
SPEAKER			
Power rating	10W 100V	6W 100V	6W 100V
Diameter	4"		5"
Cone type	Dual Cone		
Impedance (Ohm)	4	8	8
Freq response (+/- 5dB)	100 ~ 16 KHz	100 ~ 18 KHz	100 ~ 15 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz	92 dB	90 dB	93 dB
Magnet weight	7.5 oz	3.0 oz	3 oz
TRANSFORMER			
Tapping (100V line)	1 / 3 / 6 / 10W	1 / 3 / 6W	1 / 3 / 6W
Primary impedance (Ohm)	10 K / 3.3 K / 1.6 K / 1K	10 K / 3.3 K / 1.6 K	10 K / 3.3 K / 1.6 K
Secondary impedance (Ohm)	4	8	8
PHYSICAL			
Grille / enclosure	ABS with metal grille		ABS
Overall size (WxHxD)	185 x 205 x 90 mm	195 x 215 105 mm	172 x 195 x 105 mm
Weight	1.1 kg	0.75 kg	
Colour	White		