

FS420 & FS640 : FOREGROUND MUSIC SPEAKER

Available in 4" and 6" of driver size complete with matching transformer, selectable power switch and mounting bracket. They are suitable for foreground soft music such as restaurants, shops and general sound reinforcement in meeting room, corridors, etc.

Packing information

FS420 : 440 (W) x 370 (H) x 250 (D) mm
 : 9.65 kg
 : 4 uts per carton

FS640 : 420 (W) x 345 (H) x 220 (D) mm
 : 7.30 kg
 : 2 uts per carton

FS338 : FOREGROUND MUSIC SPEAKER

FS338 is built as multi purpose speaker, optimising the features of smooth and pleasant outlooks while maintaining the audio performance. Thus by its appearance and sound quality, it can be employed in most indoor venues.

It is driven by 2 x 4" PP speakers and a 1" tweeter with 40W 100V line power. It can also be driven directly from audio amplifier with 4 Ohm connections. Multiple power tapping is available via the rotary switch from 5 to 40W 100V line.

Installation is rather flexible due to its dual angle mounting bracket. They can be mounted in horizontal or vertical position. If wider coverage is required, then can be installed in horizontal array format, with two, three or 360 degree format via the optional mounting pole.

Packing information

FS338 : 560 (W) x 295 (H) x 165 (D) mm
 : 7.6 kg
 : 2 uts per carton

FS340 : FOREGROUND MUSIC SPEAKER

FS340 delivers smoothing sound with its 6" driver with tweeter. Available in 40W 100V line with power selector for level adjustment to suit area of installation. It can be installed vertically or horizontally, thanks to its flexible mounting bracket.

Be it a restaurant, pub or cafe, meeting room or lobby, FS340 shall be the exact candidate to choose from.

Packing information

FS340 : 455 (W) x 385 (H) x 240 (D) mm
 : 7.8 kg
 : 2 uts per carton



FS420
(Black / White)

4" 20W 100V



FS640
(Black / White)

6" 40W 100V



FS340

6" 40W 100V



FS338

4" 40W 100V

Technical Specifications

	FS420	FS640	FS340	FS338
SPEAKER				
Power rating	20W		40W 100V	
Diameter	4" (100 mm)	6" (150 mm)	6" (150 mm)	4" x 2 (100 mm)
Speaker type	2 way speaker with tweeter			
Impedance	8 Ohm			
Freq response (+/- 5dB)	100 ~ 18 KHz	70 ~ 18 KHz	70 ~ 16 KHz	
SPL @ 1W / m (+/- 3dB) 1 KHz	89 dB	88 dB		87 dB
TRANSFORMER				
Tapping (100V line)	1.25 / 2.5 / 5 / 10 / 20W / 8	5 / 10 / 20 / 40W / 8	5 / 10 / 20 / 40W / 8	5 / 10 / 20 / 40W / 4
Primary impedance (Ohm)	4K / 2K / 1K / 500 / 8	2K / 1K / 500 / 250 / 8		2K / 1K / 500 / 250 / 4
Secondary impedance (Ohm)		8		4
PHYSICAL				
Grille / enclosure	ABS enclosure with metal grille			
Overall size (WxHxD)	170 x 215 x 150 mm	215 x 284 x 190 mm	209 x 585 x 195 mm	137 x 385 x 262 mm
Weight	2.2 kg	3.5 kg	3.3 kg	3.4 kg
Colour	White and Black		Black	