

SP219 : UNIDIRECTIONAL SOUND PROJECTOR

SP219 is used when a more directional sound projection is required for areas such as at narrow corridors, tunnels, walkways, etc. It has aluminum body with metal grille and available with standard power rating of 10W 100V line. Mounting position can be either at wall or hung from ceiling.

Packing information

SP219 : 550 (W) x 180 (H) x 465 (D) mm
: 9.6 kg
: 4 uts per carton



SP219 : 10W 100V LINE

SP319 : BIDIRECTIONAL SOUND PROJECTOR

It is suitable for narrow corridors, or walkways that requires sound reproduction in two direction. Installing bi directional speakers may reduce the speaker counts and thus lowering installation and cabling costs.

Packing information

SP319 : 550 (W) x 180 (H) x 465 (D) mm
: 12.8 kg
: 5 uts per carton



SP319 : 10W 100V LINE BIDIRECTIONAL

HS725 : WEATHERPROOF CLEAR HORN SPEAKER

HS725 meets the requirement of speakers with horn characteristics and yet delivers sound with music clarity.

It is suitable for installations in almost any areas particularly outdoors, able to withstand rain and shine.

Packing information

HS725 : 440 (W) x 250 (H) x 370 (D) mm
: 5.1 kg
: 1 unit per box



HS725 : 30W 100V LINE

Technical Specifications

	SP219	SP319	HS725
Power rating	10W 100V		30W 100V line
Power tapping (100V Line)	Fixed at 10W		30 / 15 / 7.5 / 3.8W
Speaker	5"	2 x 5"	5" (125mm)
Primary impedance (Ohm)	1 K		333 / 667 / 1.3 K / 2.6 K
Secondary impedance (Ohm)	8		8
Frequency response (+/-3 dB @ 1 KHz)	130 ~ 15 KHz		100 ~ 10 KHz
SPL (1W / m @ 1 KHz)	91 dB		90 dB
Grille / enclosure	Mild Steel / Aluminum		Aluminum / ABS
Overall size	138 (Dia) x 205 (H) mm		366 (W) x 172 (H) x 272 (D) mm
Weight	2.9 kg	3.5 kg	3 kg
Colour	White		Light grey