



the emerging preference

speaker series

BS410 / DV410

SURFACE MOUNT SPEAKERS

BS410 is the latest addition to the speaker range with semi circle shape and higher rating of 4" speaker. They can be installed on the wall, vertically or horizontally as well as to ceilings.

Standard colour is RAL9016 pure white and other colours are available upon request.




packing information

Carton Size : 540 (W) x 410 (H) x 300 (D) mm
Weight : 13.3 kg
Qty : 12 units / carton

BS410 - 10W 100V LINE SURFACE MOUNT SPEAKER

It is constructed using high quality ABS plastic with salt tested metal grille, to enable years of lasting installation. Standard power tapping available is 1 / 3 / 6 and 10W.



Specifications

Speaker :	
Speaker type	100 mm dia dual cone
Power rating	10 W 100 V Line
Impedance	8 Ohm
Freq response (+/- 5 dB)	100 - 18 kHz
Sensitivity	92 dB @ 1 KHz
Magnet size	7.5 oz
Baffle construction	ABS with metal grille
Weight	1100 gms
Size (W x L x H)	185 x 215 x 90 mm
Transformer :	
Input voltage	70 / 100V line
Input impedance	10 K / 3.3 K / 1.6 K / 1 K Ohm
Output impedance	4 / 8 Ohm

A classic yet favourite model which delivers sound reproduction within the requirement of PA installation. Available in white colour.

Suitable for horizontal or vertical mounting, installation at ceiling as well to wall. Standard power tapping : 1 / 3 / 6 W 100 V line.

DV410 - 6W 100V LINE SURFACE MOUNT SPEAKER



packing information

Carton Size : 590 (W) x 400 (H) x 303 (D) mm
Weight : 15.4 kg
Qty : 18 units / carton

Specifications

Speaker :	
Speaker type	100 mm dia dual cone
Power rating	6W ; max 10W
Impedance	4 Ohm
Freq response (+/- 5 dB)	100 - 18 kHz
Sensitivity	92 dB @ 1 KHz, 1 m
Magnet size	3 oz
Baffle construction	ABS with metal grille
Weight	750 gms
Size	220 x 190 x 100 mm
Transformer :	
Input voltage	70 / 100V line
Input impedance	1.6 K / 3.3 K / 10 K Ohm
Output impedance	4 / 8 Ohm