

Flush mountable Over Door Lights manufactured of unbreakable polycarbonate plastic with a snap on surround to conceal the fixings.

LED lamps are 20 mm in diameter with a constant light intensity over the surface of the lamp to allow a complete 180-degree viewing angle.

Contains one, two or three low current, high light output solid state six-element LED lamps available in red, green or yellow and with each LED triggered by a separate input, either steady or flashing.

Wiring is directly to the Over Door Light outputs on Austco's range of callpoint controllers using simple single wire trigger feeds, one per colour as required, and a single 12V return wire all to screw terminal connectors on the rear of the unit. (4 wires in total for all three colours).

Mounts into a standard single gang Australian or North American wall box.

Typical power consumption is 50 mA at 12V per LED lamp when lit.

The unit's electronics are protected against power surges, near lightning strikes, cable shorts and power reversals.

Designed to comply with:

- AS 3811 Hard-wired patient alarm systems for hospitals.
- HTM Bedhead services.
- UL1069 Hospital Signalling and Nurse Call Equipment
- BS EN 60601.1, CSA 601-1-M90 &
- UL 2601.1 Medical Electrical Equipment. General Requirements for Safety.



Manufactured in general accordance with the requirements of international quality assurance standard ISO9002.

Dimensions & Specifications

Height:	115 mm	Depth:	25 mm
Width:	78 mm	Weight:	80 grams
Housing:	Unbreakable polycarbonate plastic	Plate:	N/A
Wall Box size:	Standard Australian, North American or British size wall box	Mounting Method:	Wall Box
Cable Size:	4 core 7/.20 mm (AWG 24) Data/Security cable to callpoint controller	Connectors:	Screw terminals
		Operating Temperature:	0°...50°C
		Relative Humidity Range:	0...85% (Non-condensing)