

The CM-PM pendant is a palm sized, easy to grip, one button pendant with casing manufactured of white unbreakable, impact resistant plastic.

Call button diameter size is 20 mm and available in red, orange or green. Requires 100 gm of momentary pressure to activate a pendant CALL.

Braille dots are included on the button for the sight impaired.

Comes with standard 2 m length cord made of 2 core multi-stranded double insulated white PVC cable. Longer length cable can be ordered as an optional extra.

Cord has a pendant clip attached.

The CM-PM cord has a strong plastic moulded right angle 6.5 mm plug to fit all standard Austco pendant callpoints and most other nurse/staff call systems.

When used with standard Austco pendant callpoints, removal of the pendant, either intentionally or by accident, will result in a call being

activated common to that of the pendant button. The pendant removal call/alarm can only be reset by inserting a pendant plug, or a dummy plug (supplied with the callpoint).

The CS-PMPad is a special pendant with 80 mm diameter soft touch air activating pad for use by disabled patients or others with loss of manual dexterity.

The pendants are protected against power surges, near lightning strikes, cable shorts and power reversals.

Designed to comply with:

- AS 3811 Hard-wired patient alarm systems for hospitals.
- HTM Bedhead services.
- UL1069 Hospital Signalling and Nurse Call Equipment
- BS EN 60601.1, CSA 601-1-M90 &
- UL 2601.1 Medical Electrical Equipment. General Requirements for Safety.



Manufactured in general accordance with the requirements of international quality assurance standard ISO9002.

### Dimensions & Specifications

<b>Height:</b>	95 mm	<b>Depth:</b>	N/A
<b>Width:</b>	40 mm Diameter	<b>Weight:</b>	165 grams
<b>Housing:</b>	Plastic or Rubber Moulding	<b>Plate:</b>	N/A
<b>Wall Box size:</b>	N/A	<b>Mounting Method:</b>	N/A (Plugs into Austco pendant callpoints)
<b>Cable Size:</b>	N/A	<b>Connectors:</b>	6.5 mm phone jack
		<b>Operating Temperature:</b>	0°...50°C
		<b>Relative Humidity Range:</b>	0...85% (Non-condensing)