

Entertainment Handset Outlet

Technical Specifications

Feature	Description
Height	85 mm (British Plate)
Width	85 mm (British Plate)
Depth	12 mm
Weight	80 grams
Mounting Method	Screw on Wall Box
Plate	Standard British size plate
Wall Box Size	Standard British size wall box
Temperature	0-50°C
Humidity Range	0-85% Non Condensing
Connectors	Modular to room controllers & TV controller Screw terminal to overbed lamp Pin headers to CPS-IML & RLY-2
Cable Sizes	8-way flat or round (CAT5) modular cables (AWG 26) to callpoint controller 2 x 7/.20 mm (AWG 24) multi-core cable to over bed lamp 4 core flat or round (CAT5) modular cables (AWG 26) to AM-TVC or AM-TVR 3 x 7/.20 mm (AWG 24) multi-core cable to RLY-2 (or use optional RLY-Cord)



© 2012 Austco Marketing & Service (Asia) Pte Ltd

All rights are reserved.

Austco Marketing & Service (Asia) Pte Ltd reserves the right to make changes in specifications and/or discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Compliance

Designed to comply with:



- AS 3811:1998 Hard-wired patient alarm systems for hospitals.
- AS 2999:1989 Alarm systems for the elderly and other persons at risk.
- HTM 08-03: Bedhead services.
- UL 1069 Hospital Signaling and Nurse Call Equipment.
- C-Tick Electromagnetic compatibility.
- IEC 60601-1, UL 60601-1 and CAN/CSA C22.2 No. 601.1-M90: Medical electrical equipment - Part 1: General requirements for safety.
- CE Mark of European Conformity.

Manufactured in general accordance with the requirements of international quality assurance standard ISO9002.

Product Code

CPG-1EHO/BS

Description

Callpoint LC EHO

Note: Above CPG callpoint does not include surround

Order Options

AM-CPG-XX

Singapore

Blk 5014 Ang Mo Kio Avenue 5
#05-07/08 TECHplace II
SINGAPORE 569881

+65 6481 8400
+65 6481 9400
www.austco.com.sg

Authorised Austco Reseller