

Generic Callpoint Terminal Block

Technical Specifications

Feature	Description
Height	85 mm (British Plate)
Width	85 mm (British Plate)
Depth	26 mm (Standard) 37 mm (With pendant socket)
Weight	70 grams
Housing	Wall Box
Plate	Standard British Plate
Mounting Method	Screw on
Wall Box Size	Standard British square or European round wall box
Temperature	20-50°C
Humidity Range	0-90%
Connectors	Screw terminals to callpoint controller 3-pin Header to RLY-2
Cable Sizes	6 core 7/.20 mm (AWG 24) Data/ Security cable to callpoint controller 3 x 7/.20 mm multi-core cable to RLY-2 (or use optional RLY-Cord cable assy)



© 2012 Austco Marketing & Service (Asia) Pte Ltd

All rights are reserved.

Austco Marketing & Service (Asia) Pte Ltd reserves the right to make changes in specifications and/or discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Compliance

Designed to comply with:



- AS 3811:1998 Hard-wired patient alarm systems for hospitals.
- AS 2999:1989 Alarm systems for the elderly and other persons at risk.
- HTM 08-03: Bedhead services.
- UL 1069 Hospital Signaling and Nurse Call Equipment.
- C-Tick Electromagnetic compatibility.
- IEC 60601-1, UL 60601-1 and CAN/CSA C22.2 No. 601.1-M90: Medical electrical equipment - Part 1: General requirements for safety.
- CE Mark of European Conformity.

Manufactured in general accordance with the requirements of international quality assurance standard ISO9002.

Product Code

CPG-TBxx

Description

Callpoint Terminal Block

Order Options

AM-CPG-xx

CPG-TBxx/P

Callpoint Terminal Block with Pendant Socket

Note: Above CPG Callpoints do not include surrounds

Singapore

Blk 5014 Ang Mo Kio Avenue 5
#05-07/08 TECHplace II
SINGAPORE 569881

+65 6481 8400

+65 6481 9400

www.austco.com.sg

Authorised Austco Reseller