

### CPS-1PC PULL CORD CALLPOINT

The CPS-1PC is a flush wall or ceiling mountable water resistant callpoint with pull cord for use with Austco's nurse/staff call systems to activate calls at any height from the floor by pulling on the vertical cord supplied with the callpoint. Typically installed for patients or residents to call for assistance in ensuites (wash rooms), toilets and other wet areas.

The pull cord incorporates a weak-link break point as a safety measure to break apart on the application of a mass no more than 10 kg.

The callpoint incorporates CANCEL button, in the case of the one metre cord, that lights up bright red giving visual reassurance that a call has been placed. The cancel button is manufactured from silicone rubber with anti-bacterium additive as an infection control measure.

Available as a wall mount unit with standard 1 meter nylon cord or as a ceiling mount unit with standard 3 meter nylon cord. The cord can be either red with red EMERGENCY CALL cord end tag, or green with green CALL cord end tag.



CPS-1PC PULL CORD CALLPOINT

Features	Benefits
Clear colours and concise labels.	Easy to identify and use (AS 3811 Compliant).
Low activation force.	Can be activated by the incapacitated or by those with disabilities.
Reassurance light.	Provides visual reassurance that a call has been placed.
Attractive design using unbreakable plastic plate and surround.	Impact resistant, low maintenance, long life and concealed fixings.
Weak link break point.	Prevents injury to patients and damage to callpoint.
Fits into standard wall boxes.	Uses standard electrical boxes and surrounds to meet Australian, North American or British standards.
Mounts with no sub-assemblies with modular connectors.	Installation and service times are minimised.

### Ordering Information

Code	Description	Order Options
CPS-1PC/*	Pullcord LC (1 meter cord)	Specify cord & tag /*: - Red Emergency - Green Nurse Call Size: Australian – default British – add 'BS'
CPS-1PCC/*	Pullcord Ceiling LC (3 meter cord)	
PC-Cord	Additional cord length for Pull Cord (per meter)	
<i>Note: All above pull cord callpoints include water-resistant gasket and single gang surround.</i>		