



the emerging preference

speaker series

HS815 / HS830

HORN SPEAKERS

VARIANTS

HS815 - 15W 100V LINE
HS830 - 30W 100V LINE



8" and 12" rounded aluminum flare with beige colour are available for HS815 and HS830 respectively. Both models are equipped with multiple power selection via rotary switch mounted at the rear of the speakers.

Among applications includes schools, mosques, car parks and factories which can be used indoor or under shade at outdoors.

Specifications

SPEAKER	HS815 / HS830
Power rating	15W / 30W 100V line
Impedance / Power :	1 670 Ohm (15 W) / 330 Ohm (30 W)
	2 1 K Ohm (10 W) / 670 Ohm (15 W)
	3 2 K Ohm (5 W) / 1 K Ohm (10 W)
	4 3.3 K Ohm (3 W) / 2 K Ohm (5 W)
	5 10 K Ohm (1 W) / 3.3 K Ohm (3 W)
Freq response (+/- 5 dB)	350 ~ 7 KHz / 300 ~ 10 KHz
SPL (1 W/m @ 1 KHz)	103 dB / 105 dB
Flare material	Aluminum
Dim (Dia x Length)	210 x 240 / 310 x 325 mm
Weight	1.55 / 1.85 kg
Colour	Beige



packing information

HS815 : 695 (W) x 465 (H) x 271 (D) mm
12 kg 6 uts per carton

HS830 : 665 (W) x 665 (H) x 355 (D) mm
10.6 kg 4 uts per carton



HS830



HS815

When a more directional sound projection is required, SP100 shall be the right choice, offering a clear and loud paging. Among applications are in corridors, tunnels, walkways or can be hanged from high ceiling to provide a more directional sound path.

SP100 is solidly constructed using aluminum casing which is surely able to withstand the harsh condition of environment.

Specifications

Speaker driver	5" speaker uni directional
Power rating	10 watt 100V line
Impedance	1K Ohm
Freq response (+/- 5 dB)	180 ~ 15 KHz
SPL (1 W/m @ 1 KHz)	88 dB (+/- 3 dB)
Body material	Aluminum
Dim (Dia x Length)	140 x 195 mm
Bracket	150 mm
Weight	2 kg
Colour	White



packing information

75 (W) x 75 (D) x 255 (H) mm
2.1 kg 1 uts per box